

352-001 Practice Test

Cisco ADVDESIGN

352-001: ADVDESIGN

Practice Exam: 352-001 Exams

Exam Number/Code: 352-001

Exam Name: ADVDESIGN

Questions and Answers: 240 Q&As
(CCDE)



Exam : [352-001](#)

For candidates making preparation for the Cisco 352-001 questions and answers, what they most desire is to easily pass the 352-001 (ADVDESIGN) exam. ItCertHome 352-001 includes 240 questions and answers, which are collected and collated by experts of Cisco. With our 352-001 study materials, you can successfully take Cisco certification of 352-001 exam and go further on Cisco career path.

Free 352-001 Demo

we provide Cisco 352-001 demo exam for free (in PDF format) before you decide to purchase it. Thus, you can know better about the quality of our practice exam and then make your right decision.

ItCertHome Test tool's advantages:

High Quality and Value of 352-001 exam

ItCertHome Cisco CCDE 352-001 Practice Questions is developed and finished by Cisco technical team , cover every field of the exam . Besides, we have verified 352-001 answers, almost 100% correct.

100% Guarantee to Pass 352-001 Exam

We promise to give you FULL REFUND if you fail the CCDE 352-001 certification(Cisco Certified Network Associate) with the use of our ItCertHome testing engine.

352-001 Self Test Mode

ItCertHome provides a simulated and interactive environment where you can test your knowledge and skills about 352-001 to ensure enough assurance in real testing center.

Periodic Updates of ItCertHome 352-001

Once there is some change on Cisco 352-001 exam, we will update it timely, and the product you buy will be updated within 90 days for free.

Professional and Efficient Service

We offer 7*24 customer support via diverse channels: LIVE CHAT,MAIL.Expecting the communication with you about IT certification.

The Questions & Answers cover the latest real test and with all the correct answer. we promise the Q&A for **Cisco CCDE 352-001** examination of original title complete coverage. ItCertHome **352-001 Braindumps** Questions & Answers help you pass the exam. Otherwise, we will give you a full refund.

We promised that use ItCertHome Q&A ensure you pass the exam at your first try.

1. The Q&A are from cooperation exam center of the real original title, summarized by our professional team and collated by senior IT lectured in co-training center to make sure the professional quality of the Q&A. The correctness of the Q&A is 100%, the coverage of 352-001 Q&A are more than 96%. All you need to study the whole 352-001 Q&A before you participate the certification exam, it should be possible to easily complete the exam and pass the certification.

2. ItCertHome to all the Q&A, we promised "do not pass the exam give you a full refund". If you buy our 352-001 Q&A and did not pass the exam at the first try. You can take the examination report card that stamped with PROMETRIC or VUE test centers Seal. we will refund your full cost of 352-001 Q&A, absolutely guarantee you interests have no losses.(For a full refund details)

3. ItCertHome professional IT Q&A vendors, we provide well after-sale service. To all the customers buy the Q&A, we provide track service. when you buy the Q&A with in one year. you can enjoy the upgrade Q&A service for free. If in this period, the certified test center change the 352-001 Q&A, we will update the Q&A in the first time, and provide you the download update for free.

[Cisco 352-001](#) Test belongs to one of the CCDE certified test, if needs to obtain the CCDE certificate, you also need to participate in other related test, the details you may visit the CCDE certified topic, in there, you will see all related CCDE certified subject of examination.

352-001

ItCertHome professional provide CCDE 352-001 the newest Q&A, completely covers 352-001 test original topic. With our complete CCDE resources, you will minimize your CCDE cost and be ready to pass your 352-001 tests on Your First Try, 100% Money Back Guarantee included!

This 352-001 PDF demo do not include the questions and answers's picture:

Exam : Cisco 352-001

Title : ADVDESIGN

1. Which two steps can be taken by the sinkhole technique? (Choose two.)

- A. reverse the direction of an attack
- B. redirect an attack away from its target
- C. monitor attack noise, scans, and other activity
- D. delay an attack from reaching its target

Answer: BC

2. You work as a network technician for the TIS Ltd. Study the exhibit carefully, router TIS-RA is the hub router in a Frame Relay hub-and-spoke deployment. Configure router TIS-RA's serial interface as a point-to-multipoint interface, and it is servicing three spoke routers. The link between Router TIS-RC and the frame provider experiences a service disruption, which causes the interface on Router TIS-RC to go down.

How does Router TIS-RA learn of this failure in the network and how does it react?

A. If OAM is configured between Router TIS-RA and Router TIS-RC, router TIS-RA will be notified of the failure after three missed OAM packets. After the third OAM packet is missed, the frame PVC becomes inactive, and this event terminates the routing process neighbor relationship established between Router TIS-RA and Router TIS-RC.

B. Router TIS-RA does not detect the failure in the network and its interface continues to remain in an operational state.

If routing is configured over this link, Router TIS-RA must wait for the neighbor relationship to time-out before updating its routing table to account for the lost router and its networks.

C. Router TIS-RA must wait for a full LMI status update from the provider frame switch before it is notified about the PVC status.

Once the full LMI status message is received, the routing process neighbor relationship between Router TIS-RA and Router TIS-RC is immediately terminated.

D. Router TIS-RA immediately detects the failure via LMI notification and its interface is placed in a non-operational state.

If routing is configured over this link, the neighbor relationship is terminated and the routing table is updated. The change is then propagated as appropriate to the rest of the network.

Answer: B

3. Which VPN management feature would be considered to ensure that the network had the least disruption of service when making topology changes?

- A. dynamic reconfiguration
- B. path MTU discovery
- C. auto setup
- D. remote management

Answer: A

4. What information can you get from TCP flags while assessing an attack?

- A. source of the attack
- B. type of attack
- C. target of the attack
- D. priority of the attack traffic

Answer: B

5. What is the way that an OSPF ABR uses to prevent summary route information from being readvertised from an area into the network core (Area 0)?

- A. It advertises only inter-area summaries to the backbone.
- B. It uses poison reverse and split horizon.
- C. It only sends locally originated summaries to the backbone.
- D. It compares the area number on the summary LSA to the local area.

Answer: C

6. When designing a converged network, which measures can be taken at the building access layer to help eliminate latency and ensure end-to-end quality of service can be maintained? (Choose three.)

- A. rate limit voice traffic
- B. onfigure spanning-tree for fast link convergence
- C. isolate voice traffic on separate VLANs
- D. classify and mark traffic close to the source

Answer: BCD

7. You are the Cisco Network Designer in certways.com. Which two characteristics are most typical of a SAN? (Choose two.)

- A. NICs are used for network connectivity.
- B. Servers request specific blocks of data.
- C. Storage devices are directly connected to servers.
- D. A fabric is used as the hardware for connecting servers to storage devices.

Answer: BD

8. In the network presented in the following exhibit, all routers are configured to perform EIGRP on all interfaces. All interface bandwidths are set to 1000, and the delays are configured as displayed. In the topology table at Router TIS-RC, you see only one path towards 1.1.0/24.

Why Router TIS-RC only has one path in its topology table?

- A. Router TIS-RB is not advertising 10.1.1.0/24 to Router TIS-RC due to split horizon.
- B. Router TIS-RD is not advertising 10.1.1.0/24 to Router TIS-RC because Router TIS-RC is its feasible successor.
- C. Router TIS-RD is not advertising 10.1.1.0/24 to Router TIS-RC due to split horizon.
- D. Router TIS-RB is not advertising 10.1.1.0/24 to Router TIS-RC because Router TIS-RC is its feasible successor.

Answer: C

9. The TIS company is deploying OSPF on a point-to-multipoint Frame Relay network. The remote sites need to communicate with each other and there are a relatively small number of sites (scaling is not a concern).

How to configure OSPF for this topology in order to minimize the additional routing information injected into the network and keep the configuration size and complexity to a minimum?

- A. Configure the link as OSPF nonbroadcast and manually configure each of the remote sites as a neighbor.
- B. Configure the link as OSPF broadcast and configure the hub router to always be the designated router.
- C. Configure the link as OSPF broadcast and configure a mesh group towards the remote routers.
- D. Configure the link at the hub router as OSPF point-to-multipoint and at the remote routers as OSPF point-to-point.

Answer: B

10. The IGP next-hop reachability for a BGP route is lost but a default route is available.

Assuming that BGP connectivity is maintained, what will happen to the BGP route?

- A. It will be put in a hold-down state by BGP until the next hop has been updated.
- B. It will be removed from the BGP table.
- C. It will be considered a valid route.
- D. It will be considered invalid for traffic forwarding.

Answer: C

11. How many broadcast segments are contained in this network according to the exhibit?

- A. 1
- B. 2
- C. 4
- D. 5

Answer: B

12. Which two reasons are correct about building a flooding domain boundary in a link-state network? (Choose two.)

- A. to increase the size of the Shortest Path First tree
- B. to aggregate reachability information
- C. to provide an administrative boundary between portions of the network
- D. to segregate complex and rapidly changing portions of the network from one another

Answer: BD

13. NetFlow provides valuable information about network users and applications, peak usage times, and traffic routing.

Which function is of NetFlow?

- A. monitor configuration changes
- B. monitor CPU utilization
- C. monitor link utilization
- D. generate traps for failure conditions

Answer: C

14. In the network presented in the following exhibit, all routers are configured to run EIGRP on all links. All packets transmitted during convergence are transmitted once (there are no dropped or retransmitted packets).

What is the maximum number of queries TIS-R3 might receive for 192.168.1.0/24 if the link between TIS-R1 and TIS-R2 fails?

- A. four queries, one each from TIS-R2, TIS-R4, TIS-R5, and TIS-R6
- B. no queries, because there aren't any alternate paths for 192.168.1.0/24
- C. seven queries, one from TIS-R2 and two each from TIS-R4, TIS-R5, and TIS-R6
- D. one query, since the remote routers TIS-R4, TIS-R5, and TIS-R6 are natural stubs in EIGRP

Answer: A

15. The TIS company is planning to deploy a new multicast application in its network to do real-time trading. This application will be performed simultaneously by thousands of traders located throughout the network, each a source of several IP multicast streams, to carry the "sell" and "buy" trading bids. All routers in its network have full hardware support for all PIM multicast modes.

Which mode can be used to minimize the impact of the new application on the routers in the TIS network?

- A. PIM Source Specific Multicast
- B. PIM Any-Source Multicast
- C. PIM Dense Mode
- D. PIM Bidirectional

Answer: D

16. All routers in this network are running EIGRP according to the exhibit.

Which step is the most important to make sure that this network core will converge quickly should a link failure occur?

- A. make certain the maximum number of paths on both of the routers is two
- B. make certain EIGRP is not running across non-transit links
- C. add another link between the two routers with no servers and set the metric on this new link equal to the other four links
- D. make certain EIGRP is running across all links

Answer: B

17. What is high availability?

- A. redundant infrastructure
- B. clustering of computer systems
- C. reduced MTBF
- D. continuous operation of computing systems

Answer: D

18. According to the network in this exhibit, traffic directed towards 10.1.5.1 arrives at TIS-R4. Which path will the traffic take from here?

- A. It will take TIS-R2.
- B. It will not take any path. TIS-R4 will drop the traffic.
- C. It will take TIS-R3.
- D. It will load share between TIS-R2 and TIS-R3.

Answer: A

19. Connecting an IS-IS router to four links and redistributing 75 routes from RIP.

How many LSPs will be originated by this router?

- A. one LSP: containing the router information, internal routes, and external routes
- B. six LSPs: one for each link, one containing router information, and one containing external routing information
- C. two LSPs: one containing router information and internal routes and one containing external routes
- D. three LSPs: one containing all links, one containing router information, and one containing external routing information

Answer: A

20. Lafayette Productions is looking for a new ISP that has improved availability, load balancing, and catastrophe protection. Which type of ISP connectivity solution would be best?

- A. single run
- B. multi-homed
- C. stub domain EBGP
- D. direct BGP peering

Answer: B

More [352-001 practice test](#)

Other Cisco Exams

<u>642-541</u>	<u>642-532</u>	<u>646-272</u>	<u>350-029</u>	<u>642-975</u>	<u>642-453</u>	<u>642-436</u>	<u>642-891</u>
<u>642-982</u>	<u>642-061</u>	<u>642-382</u>	<u>642-503</u>	<u>646-362</u>	<u>650-175</u>	<u>350-025</u>	<u>642-611</u>
<u>642-181</u>	<u>642-355</u>	<u>642-964</u>	<u>642-062</u>				