

642-901 Practice Test

Cisco Building Scalable Cisco Internetworks

642-901: Building Scalable Cisco Internetworks

Practice Exam: 642-901 Exams

Exam Number/Code: 642-901

Exam Name: Building Scalable Cisco Internetworks

Questions and Answers: 247 Q&As
(CCNP)



Exam : [642-901](#)

For candidates making preparation for the Cisco 642-901 questions and answers, what they most desire is to easily pass the 642-901 (Building Scalable Cisco Internetworks) exam. ItCertHome 642-901 includes 247 questions and answers, which are collected and collated by experts of Cisco. With our 642-901 study materials, you can successfully take Cisco certification of 642-901 exam and go further on Cisco career path.

Free 642-901 Demo

we provide Cisco 642-901 demo exam for free (in PDF format) before you decide to purchase it. Thus,you can know better about the quality of our practice exam and then make your right decision.

ItCertHome Test tool's advantages:

High Quality and Value of 642-901 exam

ItCertHome Cisco CCNP 642-901 Practice Questions is developed and finished by Cisco technical team , cover every field of the exam . Besides, we have verified 642-901 answers,almost 100% correct.

100% Guarantee to Pass 642-901 Exam

We promise to give you FULL REFUND if you fail the CCNP 642-901 certification(Cisco Certified Network Associate) with the use of our ItCertHome testing engine.

642-901 Self Test Mode

ItCertHome provides a simulated and interactive environment where you can test your knowledge and skills about 642-901 to ensure enough assurance in real testing center.

Periodic Updates of ItCertHome 642-901

Once there is some change on Cisco 642-901 exam, we will update it timely, and the product you buy will be updated within 90 days for free.

Professional and Efficient Service

We offer 7*24 customer support via diverse channels: LIVE CHAT,MAIL.Expecting the communication with you about IT certification.

The Questions & Answers cover the latest real test and with all the correct answer.we promise the Q&A for **Cisco CCNP 642-901** examination of original title complete coverage.ItCertHome **642-901 Braindumps** Questions & Answers help you pass the exam. Otherwise,we will give you a full refund.

We promised that use ItCertHome Q&A ensure you pass the exam at your first try.

1. The Q&A are from cooperation exam center of the real original title,summaried by our professional team and collated by senior IT lectured in co-training center to make sure the professional quality of the Q&A.The correctly of the Q&A is 100%, the coverage of 642-901 Q&A are more than 96%.All you need to study the whole 642-901 Q&A before you participate the certification exam,it should be possible to easily complete the exam and pass the certification.

2. ItCertHome to all the Q&A, we promised "do not pass the exam give you a full refund". If you buy our 642-901 Q&A and did not pass the exam at the first try. You can take the examination report card that stamped with PROMETRIC or VUE test centers Seal. we will refund your full cost of 642-901 Q&A, absolutely guarantee you interests have no losses.(For a full refund details)

3. ItCertHome professional IT Q&A vendors, we provide well after-sale service. To all the customers buy the Q&A, we provide track service. when you buy the Q&A with in one year. you can enjoy the upgrade Q&A service for free. If in this period, the certified test center change the 642-901 Q&A, we will update the Q&A in the first time, and provide you the download update for free.

[Cisco 642-901](#) Test belongs to one of the CCNP certified test, if needs to obtain the CCNP certificate, you also need to participate in other related test, the details you may visit the CCNP certified topic, in there, you will see all related CCNP certified subject of examination.

642-901

ItCertHome professional provide CCNP 642-901 the newest Q&A, completely covers 642-901 test original topic. With our complete CCNP resources, you will minimize your CCNP cost and be ready to pass your 642-901 tests on Your First Try, 100% Money Back Guarantee included!

This 642-901 PDF demo do not include the questions and answers's picture:

Exam : Cisco 642-901

Title : Building Scalable Cisco Internetworks

1. Refer to the output. What IOS command produces this output?

- A. show ip ospf
- B. show ip ospf interface
- C. show ipv6 ospf interface
- D. show ipv6 ospf

Answer: D

2. How is authentication handled with OSPFv3?

- A. OSPFv3 for IPv6 authentication is supported by SHA-1 authentication.
- B. OSPFv3 for IPv6 authentication is supported by MD5 authentication.
- C. OSPFv3 for IPv6 authentication is supported by IPv6 IPsec.
- D. OSPFv3 for IPv6 authentication is supported by IPv4 IPsec.

Answer: C

3. Refer to the exhibit. Router RTA is the hub router for routers RTB and RTC. The Frame Relay network is configured with EIGRP, and the entire network is in autonomous system 1. However, router RTB and RTC are not receiving each other's routes. What is the solution?

- A. Configure the auto summary command under router eigrp 1 on router RTA.
- B. Issue the no ip split horizon command on router RTA.
- C. Configure subinterfaces on the spoke routers and assign different IP address subnets for each subinterface.
- D. Check and change the access lists on router RTA.
- E. Issue the no ip split horizon eigrp 1 command on router RTA.
- F. Configure a distribute list on router RTA that allows it to advertise all routes to the spoke routers.

Answer: E

4. Which three restrictions apply to OSPF stub areas? (Choose three.)

- A. No virtual links are allowed.

- B. The area cannot be a backbone area.
- C. Redistribution is not allowed unless the packet is changed to a type 7 packet.
- D. The area has no more than 10 routers.
- E. No autonomous system border routers are allowed.
- F. Interarea routes are suppressed.

Answer: ABE

5. Which three IP multicast related statements are true? (Choose three.)

- A. Multicast addresses 224.0.1.0 through 238.255.255.255 are called globally scoped addresses. They are used to multicast data between organizations and across the Internet.
- B. The multicast address 224.0.0.1 is a globally scoped address that has been reserved for the Network Time Protocol (NTP) by the IANA.
- C. Multicast addresses 239.0.0.0 through 239.255.255.255 are called limited scope addresses. They are constrained to a local group or organization.
- D. Multicast addresses 224.0.0.5 and 224.0.0.6 are limited scoped addresses that have been reserved for OSPF.
- E. Multicast addresses 224.0.0.0 through 224.0.0.255 are used for network protocols on local LAN segments. Because they are always transmitted with a Time to Live (TTL) of 1, they are never forwarded by a router.

Answer: ACE

6. Refer to the exhibit. Which two statements are correct? (Choose two.)

- A. All six routes will be installed in the routing table.
- B. Two routes will be installed in the routing table.
- C. Four routes will be installed in the routing table.
- D. All the routes were redistributed into BGP from an IGP.
- E. All the routes were originated by BGP with the network command.

Answer: CD

7. Refer to the exhibit. Which two statements are true about the partial configuration that is provided. (Choose two.)

- A. All the configured neighbors are in autonomous system 100.
- B. The peer group shortens the IBGP configuration.
- C. The peer group shortens the EBGP configuration.
- D. Only the outgoing filters are applied to BGP updates.
- E. Three AS-path filters are applied to each BGP neighbor.

Answer: AB

8. Refer to the exhibit. Which three statements accurately describe the result of applying the exhibited route map? (Choose three.)

- A. The map prohibits the redistribution of all type 2 external OSPF routes with tag 6 set.
- B. The map prohibits the redistribution of all type 2 external OSPF routes.
- C. The map redistributes into EIGRP all routes that match the pfx prefix list and the five metric values 40000, 1000, 255, 1, and 1500.
- D. The map prohibits the redistribution of all external OSPF routes with tag 6 set.
- E. All routes that do not match clauses 10 and 20 of the route map are redistributed with their tags set to 8.
- F. The map permits the redistribution of all type 1 external OSPF routes.

Answer: AEF

9. Refer to the exhibit. EIGRP has been configured on all routers in the network. What additional configuration statement should be included on router R4 to advertise a default route to its neighbors?

- A. R4(config)# ip default-network 10.0.0.0
- B. R4(config)# ip route 0.0.0.0 0.0.0.0 10.1.1.1
- C. R4(config)# ip route 10.0.0.0 255.0.0.0 10.1.1.1
- D. R4(config-router)# default-information originate

Answer: A

10. Using the rules for IPv6 addressing, how can the address 2031:0000:240F:0000:0000:09C0:123A:121B be rewritten?

- A. 2031:0:240F::09C0:123A:121B
- B. 2031::240F::09C0:123A:121B
- C. 2031::240F:9C0::123A:121B
- D. 2031::240F:::09C0:123A:121B

Answer: A

11. Refer to the exhibit. On the basis of the configuration that is provided, how would the BGP updates that come from router R1 be replicated inside autonomous system 65200?

- A. All BGP updates that are received on router R2 will be sent to routers R3 and R4. Routers R3 and R4 will then forward those BGP updates to router R5.
- B. All BGP updates that are received on router R2 will not be sent to routers R3 and R4.
- C. All BGP updates that are received on router R2 will be sent directly to router R5.
- D. None of the BGP updates that are received on router R2 will ever be received by router R5.

Answer: D

12. Refer to the exhibit. Which statement is true about the router configuration that is shown?

- A. Additional DHCP options will be imported from another DHCP server.
- B. The DHCP server pools need to be bound to an interface to operate.
- C. This configuration will provide IP configuration information to two different subnets.
- D. Additional DHCP option information needs to be imported from another DHCP server.
- E. If the router hands out all the addresses in pool 1, then it will supply addresses from pool 2.

Answer: C

13. Refer to the exhibit. Which statement is true about the configuration?

- A. Hosts will receive IP settings from pool 1 until the addresses run out, and then hosts will receive the settings from pool 2.
- B. Hosts belonging to DHCP pool 1 and pool 2 will retain their IP settings for 30 hours before they must renew.
- C. Hosts in the 10.10.20.0/24 subnet will use 10.10.20.50 as its DNS server.
- D. DHCP pool 0 needs to have the ip dhcp excluded-address command to exclude the default router and DNS servers.

Answer: C

14. If no metric is specified for the routes being redistributed into IS-IS, what metric value is assigned to the routes?

- A. 0
- B. 1
- C. 10
- D. 20

Answer: A

15. Which three options are supported as address allocation mechanisms for DHCP on Cisco routers? (Choose three.)

- A. The IP address can be automatically assigned to a host.
- B. The IP address can be assigned as a random hash value of the burned-in-address of the lowest-numbered LAN interface on the router.
- C. The network administrator can assign a specific IP address to a specific host MAC address.
- D. The IP address can be assigned from configured pools in a reverse lexicographical order.
- E. The IP address can be assigned to a host for a limited time or until the host explicitly releases the address.
- F. The IP address can be assigned to a host until the host usurps the assigned value using its own dynamic override mechanism.

Answer: ACE

16. Refer to the exhibit. On the basis of the information in the exhibit, which two statements are true? (Choose two.)

- A. The output was generated by entering the show ip bgp command on the ISP router.
- B. The output was generated by entering the show ip bgp command on the SanJose1 router.
- C. The serial 0/0/1 interface on the ISP router has been configured with the set metric 50 command.
- D. The serial 0/0/1 interface on the ISP router has been configured with the set metric 75 command.
- E. When traffic is sent from the ISP to autonomous system 64512, the traffic will be forwarded to SanJose1 because of the lower MED value of SanJose1.
- F. When traffic is sent from the ISP to autonomous system 64512, the traffic will be forwarded to SanJose2 because of the higher MED value of SanJose2.

Answer: AE

17. Refer to the exhibit. Router RT-1 chooses one path to network 198.133.219.0/24. Indicate the reason Router RT-1 chooses this "best" path.

- A. In making its decision about the best path, RT-1 gives precedence to the origin code.
- B. In making its decision about the best path, RT-1 gives precedence to the BGP MED values.
- C. IP address 128.107.2.2 is lower than 128.107.255.2.
- D. In making its decision about the best path, RT-1 prefers the IGP metrics.
- E. RT-1 prefers internal BGP routes.
- F. IP address 128.107.254.2 is lower than 128.107.255.2.

Answer: A

18. What are the two reasons for the appearance of 0.0.0.0 as the next hop for a network in the show ip bgp command output? (Choose two.)

- A. The network was originated via redistribution of an interior gateway protocol into BGP.
- B. The network was defined by a static route.
- C. The network was originated via a network or aggregate command.
- D. The network was learned via EBGP.
- E. The network was learned via IBGP.

Answer: AC

19. Which three IP multicast group concepts are true? (Choose three.)

- A. If a packet is sent to a multicast group address, all members of the multicast group will receive it.
- B. If a packet is sent to a multicast group address, the multicast frame contains the source multicast address.
- C. A router does not have to be a member of a multicast group to receive multicast data.
- D. A router does not have to be a member of a multicast group to send to the group.
- E. A router must be a member of a multicast group to receive multicast data.
- F. A router must be a member of a multicast group to send to the group.

Answer: ADE

20. What are two rules for compacting IPv6 addresses? (Choose two.)

- A. The maximum number of times a double colon can replace a 16-bit segment that consists of all zeroes is two.
- B. The leading zeroes in any 16-bit segment do not have to be written.
- C. Every 16-bit segment that consists of all zeroes can be represented with a single colon.
- D. The trailing zeroes in any 16-bit segment do not have to be written.
- E. Any single, continuous string of one or more 16-bit segments that consists of all zeroes can be represented with a double colon.
- F. Two zeroes in the middle of any 16-bit segment do not have to be written.

Answer: BE

21. Refer to the exhibit. Which statement is true?

- A. Router RAR1 will accept only route 10.10.0.0/19 from its BGP neighbor.
- B. Router RAR1 will send only route 10.10.0.0/19 to its BGP neighbor.
- C. Only traffic with a destination from 10.10.0.0/19 will be permitted.

D. Only traffic going to 10.10.0.0/19 will be permitted.

Answer: A

22. Refer to the exhibit. On the basis of the output, what two conclusions can be reached? (Choose two.)

- A. Three physical interfaces are taking part in integrated IS-IS.
- B. Address summarization is configured.
- C. There are two neighboring routers sending IS-IS routing information.
- D. The default administrative distance has been changed.
- E. IS-IS is not redistributing any other routing protocols.
- F. IS-IS is not enabled.

Answer: CE

23. What is the difference between the IPv6 addresses ::/0 and ::/128?

- A. ::/0 is the unspecified address, and ::/128 is the multicast address.
- B. ::/0 is the unicast address, and ::/128 is the anycast address.
- C. ::/0 is the unicast address, and ::/128 is the multicast address.
- D. ::/0 is the anycast address, and ::/128 is the multicast address.
- E. ::/0 is the default route, and ::/128 is the unspecified address.
- F. ::/0 is the anycast address, and ::/128 is the default address.

Answer: E

24. Refer to the exhibit. This network is running IS-IS. Router RTC is inside Cloud#1. From the output on RTD, which two statements are true? (Choose two.)

- A. The SNPA for RTE is the source data link address that is used to transmit frames to RTD.
- B. IP routing updates between RTC and RTD will be IP datagrams that are encapsulated by HDLC.
- C. IP routing updates between RTC and RTD will be IP datagrams that are encapsulated by CLNS.
- D. IP routing updates between RTC and RTD will be CLNS datagrams that are encapsulated by HDLC.
- E. Because it is running IS-IS in IP-only mode, RTD will not transmit CLNS packets.
- F. The NET for RTE will be 49.0150.0019.06b7.fd5f.00.

Answer: AD

25. Refer to the exhibit. Router RT-1 and router RT-2 both advertise network 131.25.0.0/16 to router RT-3 via internal BGP. What is the reason that router RT-3 chose router RT-1 as its best path to network 131.25.0.0/16.

- A. It advertises the best AS-path.
- B. It advertises the best origin code.
- C. It advertises the best MED.
- D. It advertises the best local preference.
- E. It has a better router ID.
- F. It advertises a lower autonomous system.

Answer: E

26. Refer to the exhibit. What two statements are true about the IS-IS configuration? (Choose two.)

- A. The router is in area 49.0001.0002.
- B. The router has a system ID of 0003.0004.
- C. The router acts as a Level 1-2 router.
- D. The network service access point selector (NSEL) byte has a value of 0.
- E. CLNS routing is enabled for the router.

Answer: CD

27. Refer to the exhibit. Which configuration would correctly enable Host A to acquire an IP address from the DHCP server that is located at 10.1.2.10/24?

- A. ASw1(config)# interface range FastEthernet 0/1 - 24
ASw1(config-if-range)# ip forward-protocol udp 67

ASw1(config-if-range)# ip forward-protocol udp 68
B. ASw1(config)# interface range FastEthernet 0/1 - 24
ASw1(config-if-range)# ip helper-address 10.1.2.10
C. RTA(config)# interface fastethernet0/0
RTA(config-if)# ip forward-protocol udp 67
RTA(config-if)# ip forward-protocol udp 68
D. RTA(config)# interface fastethernet0/1
RTA(config-if)# ip forward-protocol udp 67
RTA(config-if)# ip forward-protocol udp 68
E. RTA(config)# interface fastethernet0/0
RTA(config-if)# ip helper-address 10.1.2.10
F. RTA(config)# interface fastethernet0/1
RTA(config-if)# ip helper-address 10.1.2.10
Answer: E

28. Into which two types of areas would an area border router (ABR) inject a default route? (Choose two.)

- A. the autonomous system of a different interior gateway protocol (IGP)
- B. area 0
- C. totally stubby
- D. NSSA
- E. stub
- F. the autonomous system of an exterior gateway protocol (EGP)

Answer: CE

29. A router has two paths to reach another network in a different autonomous system. Neither route was generated by the local router and both routes have the same default weight and local preference values. Which statement is true about how BGP would select the best path?

- A. If the command `bgp always-compare-med` has been given, then the router will prefer the route with the highest MED.
- B. The router will prefer the route with the lower MED.
- C. The router will prefer the shortest autonomous system path.
- D. To influence one route to be preferred, its default local preference value will be changed via the use of the command `bgp default local-preference 50`.

Answer: C

30. Refer to the exhibit. Router R1 is being used as a relay device for autoconfiguration of switch S1. Which configuration will accomplish this?

- A. S1(config)# interface fastethernet 0/1
S1(config-if)# ip helper-address 10.0.0.2
- B. S1(config)# interface fastethernet 0/1
S1(config-if)# ip helper-address 20.0.0.1
- C. R1(config)# interface fastethernet 0/0
R1(config-if)# ip helper-address 20.0.0.2
R1(config-if)# ip helper-address 20.0.0.3
R1(config-if)# ip helper-address 20.0.0.4
R1(config-if)# exit
R1(config)# interface fastethernet 0/1
R1(config-if)# ip helper-address 10.0.0.1
- D. R1(config)# interface fastethernet 0/0
R1(config-if)# ip helper-address 20.0.0.1
R2(config)# interface fastethernet 0/0
R2(config-if)# ip helper-address 20.0.0.1
R3(config)# interface fastethernet 0/0

```
R3(config-if)# ip helper-address 20.0.0.1
R4(config)# interface fastethernet 0/0
R4(config-if)# ip helper-address 20.0.0.1
E. S1(config)# interface fastethernet 0/1
S1(config-if)# ip helper-address 10.0.0.2
R2(config)# interface fastethernet 0/0
R2(config-if)# ip helper-address 20.0.0.1
R3(config)# interface fastethernet 0/0
R3(config-if)# ip helper-address 20.0.0.1
R4(config)# interface fastethernet 0/0
R4(config-if)# ip helper-address 20.0.0.1
Answer: C
```

More [642-901 practice test](#)

Related 642-901 Exams

[642-892](#) *Composite Exam*

[642-901](#) *Building Scalable Cisco Internetworks*

[642-825](#) *Implementing Secure Converged Wide Area Networks*

[642-812](#) *Building Cisco Multilayer Switched Networks*

[642-845](#) *Optimizing Converged Cisco Networks*

[642-801](#) *Building Scalable Cisco Internetworks(BSCI)*

[642-811](#) *Building Cisco Multilayer Switched Networks (BCMSN)*

[642-891](#) *Composite Exam*

[642-746](#) *Implementing Cisco Unified Wireless Mobility Services*

[642-821](#) *Building Cisco Remote Access Networks (BCRAN)*

[642-831](#) *Cisco Internetwork Troubleshooting (CIT)*

[642-902](#) *implementing cisco ip routing*

[642-813](#) *implementing cisco switched networks*

[642-832](#) *Troubleshooting and maintaing cisco ip networks*

Other Cisco Exams

642-456	642-611	642-355	642-274	642-053	642-382	642-112	640-816
642-504	642-272	650-621	642-055	646-230	642-071	646-562	642-176
646-011	642-061	646-056	642-961				